# 3M<sup>™</sup> Double Coated Tape GPT-020F

### **Application Ideas**













Aluminum

Glass

- ▶ POP/POS displays
- Light boxes
- ▶ Indoor-outdoor signs
- ▶ Paper bonding and packaging
- Metal fabrication
- Splicing and bonding

- ▶ Home decoration
- Mounting of plastic parts
- Mounting in electronics
- ► Furniture trim attachment

# Bonds to many high surface energy substrates and some low surface energy substrates, including:

Stainless steel Acrylic PP HDPE ABS Polycarbonate

- Sports equipment
- ▶ Trim attachment in appliance

#### **Product Characteristics**

- ▶ Excellent peel performance on a variety of substrates
- Excellent initial adhesion on most LSE and HSE surfaces
- ► Superior high temperature shear performance
- ▶ Competitive market price tier-B solution
- ► Solventless adhesive technology
- ▶ High thermal and humidity resistance
- ► Easy handling and converting due to film liner delivery

## **Top Markets**



Specialty Vehicle











**Appliance** 



Outdoor Power Equipment



3M ID	Size	
AT010788878	GPT-020P DCT Paper Liner 12MM X 50M	
AT010788886	GPT-020P DCT Paper Liner 19MM X 50M	
AT010788894	GPT-020P DCT Paper Liner 25MM X 50M	
AT010788902	GPT-020P DCT Paper Liner 50MM X 50M	
AT019499055	GPT-020P DCT Paper Liner 500MM X 50M	
GPT-020F Double Coated Tape FILM LINER		
AT010788928	GPT-020F DCT Film Liner 12MM X 50M	
AT010788936	GPT-020F DCT Film Liner 19MM X 50M	
AT010788944	GPT-020F DCT Film Liner 25MM X 50M	
AT010788951	GPT-020F DCT Film Liner 50MM X 50M	
GPT-020P & GPT-020F LOG ROLL Format		
UU011691639	GPT-020P DCT Paper Liner 1000MM X 50M	
UU010956199	GPT-020F DCT Film Liner 1540MM X 50M	

**GPT-020P Double Coated Tape PAPER LINER** 

Technical Details	
Adhesive	Solventless acrylic
Carrier type (thickness)	PET 12 micron (0.5 mil)
Liner type (thickness)	White PP 100 micron (4 mil)
Total tape thickness without liner	200 micron (8 mil)
Short term temp. performance	190°C
Long term temp. performance	90°C
Color	Transparent

