

# HEARING PROTECTION CLASSIC EARMUFFS

PRODUCT DATA SHEET: EMCLA



PRODUCT CODE:  
EMCLA



## FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5  $SLC_{80}$  27dB.
- Hearing protection for noise levels to 110dB(A).
- Lightweight, comfortable and economical.
- High Level 27dB  $SLC_{80}$  hearing protection.
- Adjustable headband for easy fit and greater comfort.
- Headband equalizes pressure and ensures cushions stay in position.
- Minimal pressure on the top of the head with its comfort headband.
- Soft, wide cushions fit comfortably around the ears.

## CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use.

## APPLICATIONS

The Pro Choice Safety Gear range of hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.



ADJUSTABLE



COMFORT



REUSABLE



LIGHTWEIGHT

## PRODUCT DETAILS

Weight:	151g
Clamping Force:	11.6N
Colour:	Black
Size:	Adjustable

## AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
EMCLA	BLACK	EACH	1	25

## TEST DATA

ATTENUATION TABLE (IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	16.6	14.5	23.4	34.0	34.8	39.2	38.0
Standard Deviation	3.1	2.1	3.8	3.1	1.9	3.5	3.4
Mean-Minus-Standard Deviation Attenuations	13.5	12.4	19.6	30.9	32.9	35.7	34.6

$SLC_{80}$  Value is 27dB (Class 5)

## STANDARDS

**CERTIFIED TO:**  
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5  $SLC_{80}$  27dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 110dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



AS/NZS 1270:2002  
SMK 40540

**PARAMOUNT SAFETY PRODUCTS AUSTRALIA**  
12 FELLOWSHIP ROAD,  
GNANGARA, WA 6077  
TECH SUPPORT: 1300 275 820  
CUSTOMER SERVICE: 1300 770 723  
EMAIL: INFO@PROCHOICESAFETYGEAR.COM

**PARAMOUNT SAFETY PRODUCTS NEW ZEALAND**  
7 SIR WOOLF FISHER DRIVE, HIGHBROOK,  
EAST TAMAKI, AUCKLAND 2013  
TECH SUPPORT: 0800 888 778  
CUSTOMER SERVICE: 0800 888 778  
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM  
PARAMOUNTSAFETY.COM

**PRO**  
PRO CHOICE SAFETY GEAR  
FROM  
**PARAMOUNT**  
SAFETY PRODUCTS