

## **TECHNICAL DATA SHEET**

**Product Type:** Flat back Kraft Paper Tape

Colour: Brown

**Roll Size:** 12mm to 1400mm in 50m Lengths

Adhesive: **Rubber Natural** 

**Description:** A Brown coloured Kraft Paper Tape coated one side with a natural

rubber resin adhesive.

**Application:** Designed for a wide range of packaging, joining, splicing and

> tabbing applications within the paper and cardboard industry. The product can be used for picture framing and exhibits good adhesion to a wide range of surfaces. The product provides a quick and

positive seal under a wide range of temperature and humidity

conditions.

**Technical Details:** 0.19mm Gauge:

> 180° Peel Adhesion: 4.4 N/cm Tensile Strength: 60 N/cm Service Temperature: 0°C to 60°C

Surface Preparation: The surface on which the tape is to be used must be clean, dry and

> free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended

application temperature is between 15°C and 30°C.

Storage: Tapes stored below the minimum application temperature will

require warming up to that level before use. Up to 24 hours may be

required for this to take place.

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values BUT CANNOT accept any responsibility or liability direct or cons equential for loss or damage caused as a result of our recommendations.

