

## **TECHNICAL DATA SHEET**

**Product Type:** Double Sided Paper Tape

Colour: Cream

**Roll Size:** Required Widths in 33m Lengths

Adhesive: **Rubber Natural** 

**Description:** Paper with rubber based adhesive on both sides with a white creped

silicon release liner.

**Application:** 1. Main use - for adhering Golf Grips

2. General Purpose

3. Point of Sale

**Technical Details:** Gauge: 0.19mm

Liner Thickness: 0.14mm Tensile Strength: 32 N/cm Adhesion to Steel: Open Side 2.2 N/cm Closed Side 2.2 N/cm

Service Temperature: 0°C to +60°C Storage Temperature: 15°C to 25°C Shelf Life: 12 Months

Surface Preparation: The surface on which the tape is to be used must be clean, dry and

> free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application

temperature is between 15°C and 25°C.

Storage: Tapes stored below the minimum application temperature will require

warming up to that level before use. Up to 24 hours may be required

for this to take place.

Values: All values presented have been determined by standard test methods and are average values only.

Recommendations: Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

Warranty: We can only warranty our products to the level that they are consistent with our Product Information Sheet values BUT CANNOT accept any responsibility or liability direct or conequential for loss or damage caused as a result of our recommendations.

