

|                      |   |
|----------------------|---|
| <b>Product Type:</b> | US Gaffer Tape  |
| <b>Colour:</b>       | Black, Silver, White                                      |
| <b>Roll Size:</b>    | 6mm to 1,450mm in 40m Lengths<br>Retail packed 48mm x 40m |
| <b>Adhesive:</b>     | Rubber Natural  |



**Description:** Polyethylene co-extruded cloth with an aggressive high coat weight Rubber adhesive. Designed for applications requiring high tensile and adhesive shear strengths.

**Application:** A high quality USA waterproof cloth "Gaffer" Tape for entertainment industry (shows good resistance to plasticiser migration for use on cables), Auto Trade/Race Tape, Surface Protection for sandblasting, Joining/Sealing of filmic, Materials (including hydroponics – white cloth), Heating Ventilation & Air Conditioning Ductwork, Asbestos & Hazardous Waste Disposal.

|                           |                                |              |
|---------------------------|--------------------------------|--------------|
| <b>Technical Details:</b> | Gauge:                         | 0.37mm       |
|                           | Tensile Strength:              | 78 N/cm      |
|                           | Elongation at Break (PSTC-31): | 14%          |
|                           | Adhesion to Steel (PSTC-1):    | 10.9 N/cm    |
|                           | Service Temperature:           | 5°C to 90°C  |
|                           | Storage Temperature:           | 15°C to 25°C |
|                           | Shelf Life:                    | 12 Months    |

**Surface Preparation:** The surface on which the tape is to be used must be clean, dry and free from grease and dust. Remember that pressure sensitive adhesive must be applied with the maximum possible pressure in order to achieve maximum adhesion levels. The recommended application temperature is between 15°C and 30°C.

**Storage:** Tapes stored below the minimum application temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

**DISCLAIMER:**

**Values:** All values presented have been determined by standard test methods and are average values only.

**Recommendations:** Whilst we are happy to recommend products from our range for applications, it is imperative that the customer/user complete their own tests to determine suitability for their application under "working conditions" and if longevity is important, that ageing tests be carried out.

**Warranty:** We can only warranty our products to the level that they are consistent with our Product Information Sheet values

**BUT CANNOT accept any responsibility or liability direct or consequential for loss or damage caused as a result of our recommendations.**