

TensorGrip®

700

CLEANER



METALS



MOTORS



TOOLS



CONCRETE



PRINTING PRESSES



ALMOST ANY
DIRTY OR GREASY
SURFACE

TECHDATA

PRODUCT DESCRIPTION

TensorGrip® 700 Cleaner is a versatile solvent engineered for many applications. This powerful cleaner prepares surfaces for adhesive bonding and efficiently removes oil and grease residues. Ideal for diverse clean-up tasks, it comes in a convenient aerosol can with an extension tube for precise application and easy access to hard-to-reach areas.

ADVANTAGES

- Multi-purpose solvent and cleaner
- Leaves surfaces spotless with no residue
- Safe for use on most surfaces
- Controlled drying rate for optimal results
- Extension tube for precise application
- Effectively softens old and stubborn tape adhesives

DIRECTIONS FOR USE

1. Use with adequate ventilation. We recommend shaking the Aerosol well before using it.
2. Turn the spray so the arrow points towards the dot on the valve rim.
3. Hold the can at a 90-degree angle. Spray approximately 150mm to 200mm from the surface.
4. Allow the cleaner to remain on the surface for a few seconds.
5. While wet, wipe it off using a clean cloth or tissue to obtain a residue-free, clean surface.
6. For very obstinate adhesive, allow the cleaner to come in contact with the adhesive longer before wiping, or you may need to apply successive applications.
7. Avoid re-using the already used area of the cloth or tissue to avoid re-contamination.
8. For hard-to-reach areas, insert the extension tube for a more precise application.
9. To separate previously bonded items, start at one edge of the bond and spray the solvent into the seam. Gently lever the bond apart while working more solvent into the bond line.
10. Before use, check compatibility by spraying a small patch test of the cleaner on the substrate.

Tensorgrip®

700

CLEANER

AVAILABLE IN



AEROSOL
500 ML

CHEMICAL TECHNICAL DATA

TYPICAL PROPERTIES

Physical State	Liquified Gas
Relative density (Water = 1)	0.71
Flash point (°C)	-1
Flammability	Highly Flammable
Solubility in water	Immiscible
SHELF LIFE	18 months from date of manufacture

HANDLING & STORAGE

- Consult the Material Safety Data Sheet before use.
- Do not store at temperatures over 50°C.
- Avoid exposure to direct sunlight.
- Always test the product to determine suitability for your particular application before use in production.

Copyright © 2024 by Quin Global AU Ltd All rights reserved. This publication or any portion thereof may not be reproduced or used in any manner whatsoever without the express written permission of the publisher.

DISCLAIMER OF WARRANTY: The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.



Quin Global AU
63 Hincksman St, Queanbeyan NSW 2620
1300 857 846 • www.tensorglobal.com

