



tesa[®] 58663

Product Information



Heavy Duty Cloth Tape for applications requiring high strength and holding power. Ideal for sandblasting

Product Description

tesa 58663 PVC cloth tape combines a heavy duty PE laminated cloth backing with a high strength natural rubber adhesive. The natural rubber adhesive allows for easy application and strong holding power on many rough and hard to stick surfaces such as carpet and many plastics. The heavy duty PE laminated cloth backing is waterproof, abrasive resistant and provides short term temperature resistance up to 93°C, making it suitable in even the toughest conditions.

Applications

tesa 58663 Heavy Duty Cloth Tape is well suited for a wide range applications where high strength and holding power are required.

Application ideas:

- Ideal for masking up during sandblasting applications
- Joining builders film
- Bundling cables and securing wires on carpet
- Sealing heavy cartons or boxes
- Book binding
- Demarcation

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|--------------------|-------------------|--------|
| • Backing | PE laminated cloth | • Total thickness | 330 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------------------|-------|
| • Elongation at break | 7.5 % | • Easy to write on | no |
| • Tensile strength | 79 N/cm | • Hand tearability | good |
| • Easy to remove | no | • Temperature resistance (30 min) | 93 °C |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 6 N/cm |
|---------|--------|



tesa[®] 58663

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=58663>