

## tesa<sup>®</sup> 4713 Paper Standard

### **Product Information**



tesa® 4713 – Packaging Tape with Paper from Responsible Sources

#### **Product Description**

tesa® 4713 is a general-purpose packaging tape based on a fine crepe paper backing and a natural rubber adhesive. The paper backing of tesa® 4713 is made with paper from well-managed, certified forests and other controlled sources (FSC® C148769). The natural rubber adhesive system features good adhesion to multiple surfaces as well as good tack.

#### **Application Fields**

- Sealing of cardboxes
- Suitable for light-weight packaging
- Good adhesion in recycled cardboards
- Brand showcase and advertisement purposes
- Suitable for manual and automatic dispensers
- Recycling-friendly tape according to INGEDE method 12

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

<ul><li>Backing material</li><li>Type of adhesive</li></ul>	Paper natural rubber	Total thickness	125 μm
Properties/Performance Values			
<ul> <li>Automatic application</li> </ul>	yes	<ul> <li>Manual application</li> </ul>	yes
<ul> <li>Elongation at break</li> </ul>	8 %	<ul> <li>Printability</li> </ul>	good
<ul> <li>Hand tearability</li> </ul>	very good	Tensile strength	30 N/cm

#### Adhesion to Values

• steel 2.8 N/cm

#### **Additional Information**

tesa® 4713 is available in chamois (brown) and white.



# tesa® 4713 Paper Standard

**Product Information** 

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

