



OUR PACKAGING TAPES

Simplified Packaging Assortment

We've simplified our range of packaging tapes, however rest assured that there are no changes to our products- Our high quality packaging tapes remain untouched.

The only change is with our product codes. We have changed our product codes for internal harmonisation. Our product codes now contain an adhesive type within the product code. Those ending in 'A' represent an Acrylic adhesive, while those ending with an 'NR' represent a Natural Rubber adhesive.

These changes have been essential to:

- Create global alignment within our company
- Actively promote these products online
- Simplify our product codes with an adhesive style code (A = Acrylic, NR = Natural rubber)
- Ensure long-term price stability

For any questions or further information, please contact your tesa sales representative, or our friendly customer service team.

NEW product Code	Old product Code	Adhesive
4260A	4260	Acrylic
4262A	4262	Acrylic
4266A	4276	Acrylic
4256NR	4263	Natural rubber
4259NR	4266	Natural rubber

Same Great Products, Same Great Price

tesa® Packaging Tape Assortment

Acrylic Packaging Tapes

Product	Adhesive	Backing thickness [µm]	Total thickness [µm]	Adhesion to steel [N/cm]	Tensile strength [N/cm]	Cold room [1°C - 4°C]	Freezers [-40°C]	Hard to adhere surfaces	Recycled board	Heavy packing
tesa® 4260A	Acrylic	25	45	1.9	40	•••	•••	•	•	•
tesa® 4262A	Acrylic	30	52	2.1	45	•••	•••	•	••	••
tesa® 4266A	Acrylic	40	65	2.4	60	•••	•••	•	••	•••

••• Good •• Medium • Low

Natural Rubber Packaging Tapes

Product	Adhesive	Backing thickness [µm]	Total thickness [µm]	Adhesion to steel [N/cm]	Tensile strength [N/cm]	Cold room [1°C - 4°C]	Freezers [-40°C]	Hard to adhere surfaces	Recycled board	Heavy packing
tesa® 4256NR	Natural rubber	28	47	2.5	40	••	••	••	•••	••
tesa® 4259NR	Natural rubber	32	55	2.6	52	••	••	••	•••	•••

••• Good •• Medium • Low

Coloured Packaging Tapes

Product	Adhesive	Backing thickness [µm]	Total thickness [µm]	Adhesion to steel [N/cm]	Tensile strength [N/cm]	Cold room [1°C - 4°C]	Freezers [-40°C]	Hard to adhere surfaces	Recycled board	Heavy packing
tesa® 64204	Acrylic (solvent)	28	55	3	35	•••	•••	•••	•••	••
tesa® 4104	Natural rubber		67	3.6	60	•••	•••	•	••	•••

••• Good •• Medium • Low

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

tesa tape Australia Pty Ltd
Phone: 1800 226 851
Email: sales.australia@tesa.com

tesa tape New Zealand Ltd
Phone: 0800 037 269
Email: sales.nz@tesa.com